# ELITE CARE 3 IN 1 PUTTY MIX



#### Profile

3 in 1 putty mix is a advance technology for high-performance penetrating putty mix used to protect concrete, brick, mortar and masonry surfaces from the damaging effects of water intrusion.

It is a styrene co-polymer and water-based advance technology solution. It is a unique one of its kind self-primed putty which provides a strong foundation for topcoats and enhances the desired performance of finish paints, both in looks and durability.

#### **Recommended Uses:**

3 in 1 Putty Mix is to be used only on interior surfaces. The putty can be applied on all concrete and masonry surfaces. No primer needed.

## Features and Benefits:

- It is cost-effective and have sealer, putty and damp care properties, no need to apply putty or sealer separately.
- Provides excellent water repellency and keeps water out of your structure.
- Does not change the appearance of the surface.
- Easy to apply.
- Ready to use.
- It provides excellent top coat finish.
- The putty offers superior smoothness.
- Resists mildew and moss formation, rust stains and efflorescence
- Requires no special tools to apply
- Can be used for outdoor or indoor

<b>Technical Information:</b>	
PROPERTIES	RESULTS
Appearance Solid Volume Density g/cm3 (lb. /cu. in.)	Milky white 48 1.55
pH VOC PVC type	8 < 20 g/L High
Viscosity DFT Theoretical Coverage	120-140 poise 100 Micron 65 sft/ltr

#### **Application:**

- a) Apply as sealer: Mix 30 40% water then apply one coat as sealer.
- b) Apply as putty: Without mixing water apply directly to fill porosity of wall and let it dry for 24 hours, after drying scrap the wall by a series paper(no 120) and make the surface even



## ELITE CARE 3 IN 1 PUTTY MIX



#### Safety:

Read the Safety Data Sheet (SDS) for this product. For professional use only. This product may irritate eyes, skin and the respiratory tract. Avoid contact with skin or eyes. Avoid breathing mist. Wear long sleeves, safety goggles and impervious gloves.

#### Packaging:

3 in 1 Putty Mix is available in 5KG (Gallon) & 25KG (Drum).

#### Storage /shelf Life:

Damp stop Putty Sealer has a shelf life of 2 years for unopened containers.

### **Precautions & Limitations:**

As with all chemical products, so shake properly and care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which can also be tainted with vapour until product fully cured or dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children and animals. Reseal containers after use. Do not reuse containers for storage of consumable item. For further information refer to the material safety data sheet.

## Disclaimer

The information in this document is given to the best of Elite's knowledge, based on laboratory testing and practical experience. Elite's products are considered as semi-finished goods and as such, products are often used under conditions beyond Elite's control. Elite cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Elite reserves the right to change the given data without further notice.

Users should always consult Elite for specific guidance on the general suitability of this product for their needs and specific application practices.









Sealer 50 quired C

Hotline: 09666733733



### ELITE PAINT & CHEMICAL INDUSTRIES LTD.